WHAT IS CLAIMED IS:

1. A pump comprising:

a housing;

a pump inlet;

a pump outlet;

a drive shaft provided within the housing; and

multiple stages provided within the housing, each stage further comprising:

a body further comprising:

a fluid inlet;

a fluid outlet; and

an interior volume between the fluid inlet and the fluid outlet;

an impeller provided in the interior volume and coupled to the drive shaft;

a vent allowing fluid communication between the interior volume and a volume outside of the body.

2. The pump of Claim 1, wherein the body further comprises:

a central wall dividing the interior volume into a first volume and a second volume, wherein the central wall further comprises:

a central aperture provided in the wall; and

at least one aperture spaced radially outward from the central aperture.

3. The pump of Claim 2, wherein the central wall further comprises vanes adapted to direct fluid from the at least one aperture radially inward toward the central aperture.

4. The pump of Claim 3, wherein the body includes

at least five vanes; and

at least five apertures spaced radially outward from the central aperture.

5. The pump of Claim 3, wherein the body further comprises:

a first wall provided on a first side of the central wall;

a second wall opposite the first wall, and provided on a second side of the central wall;

wherein the drive shaft extends through the first wall and the second wall.

6. The pump of Claim 5, wherein the fluid inlet is provided in the first wall, and the fluid outlet is provided in the second wall.

7. The pump of Claim 6, wherein the drive shaft extends through the fluid inlet and the fluid outlet.

8. The pump of Claim 2, wherein the drive shaft extends through the central aperture.

9. The pump of Claim 9, wherein the central aperture is substantially sealed against fluid flow, but allows rotation of the drive shaft relative to the body.

10. A pump comprising:

a pump casing;

a shaft provided within the pump casing;

a plurality of fluid handling units wherein at least one fluid handling unit comprises:

a housing;

a wall provided within the housing, the wall having a first surface and a second surface, the wall separating the housing into a first volume associated with the first surface and a second volume associated with the second surface, the wall configured to allow the passage of a fluid from the first volume to the second volume;

a vent provided in the housing, the vent being in fluid communication with the first volume or second volume, and a volume external of the housing;

an impeller disposed in the first volume, the impeller being coupled to the shaft.

11. The pump of Claim 10, wherein the vent is a notch.

12. The pump of Claim 10, further comprising a plurality of vanes provided in the second volume, the vanes being adapted to direct the flow of fluid between the first and second volumes.

13. The pump of Claim 12, wherein the plurality of vanes are provided on the second surface.

14. The pump of Claim 10, wherein the at least one fluid handling unit is a lower pressure fluid handling unit.

15. The pump of Claim 10, wherein the lower pressure fluid handling unit is a first stage in the pump.

16. A method of repairing a pump, the pump having a relatively low pressure fluid handling module, and a relatively high pressure fluid handling module, the low pressure module and the high pressure module each having an outer casing, the method comprising:

venting the outer casing of the low pressure fluid handling module.

17. The method of Claim 16, wherein venting the outer casing further comprises providing a notch in the outer casing.

18. The method of Claim 17, wherein providing the notch further comprises drilling a hole in the outer casing.

19. The method of Claim 16, wherein venting the outer casing further comprises replacing the low pressure fluid handling module with a fluid handling module having a vent.

20. A module for use in a fluid handling system, the module comprising:

a housing;

a wall provided within the housing having a first surface and a second surface, the wall separating the housing into a first volume associated with the first surface and a second volume associated with the second surface, the wall configured to allow the passage of a fluid from the first volume to the second volume; and

a vent provided in the housing, the vent in communication with either the first volume or second volume, and a volume external of the housing.

21. The module of Claim 20, wherein the vent is a notch.

22. The module of Claim 20, further comprising a plurality of vanes provided in the second volume, the vanes being adapted to direct the flow of fluid between the first volume and second volume.

23. The module of Claim 22, wherein the plurality of vanes are provided on the second surface.

24. The module of Claim 20, wherein the first volume is configured to receive an impeller.

25. The module of Claim 20, further comprising a first plate coupled to a first end of the housing, the first plate associated with the first volume.

26. The module of Claim 25, further comprising a second plate coupled to a second end of the housing, the second plate associated with the second volume.

27. The module of Claim 20, further comprising a second plate coupled to a second end of the housing, the second plate associated with the second volume.